

# Pointfix<sup>®</sup> All Weather Epoxy Jointing Mortar

**Pointfix** is a superior multi-purpose jointing and repair mortar that comes premixed with resins. This means there is no liquid to measure and mix and is easier to mix compared to sands or cement mortar. **Pointfix** comes as a two pack epoxy resin-based pointing mix that is specifically designed for pointing and infilling between many types of surfaces including concrete, natural stone, brick work and stone work.

## Uses

We all know if it rains, or is forecast to rain, completing a project can become a major problem; especially when trying to point bricks and slabs. **Pointfix** eliminates this issue as it can be applied in the rain and can even cure under water.

**Pointfix** comes in a range of colours allowing a wide choice of design and gives consistent colour mixes. The 1:1 mixing ratio means you only use what is needed from the packs, cutting down on waste. **Pointfix** can be stored until required and leftover product can even be mixed with other colours.

## How to Apply Pointfix

- Mix the **Pointfix** packs A and B together in a 1:1 ratio thoroughly;
- Add water and mix; if too much water is added, simply pour out the excess. For quicker applications, there is no need to add water, just apply with a clean soft broom;
- Use this mixture to point slabs and bricks as normal brushing off any excess product;
- Leave to cure for **12 hours at 15-20 °C**; please note curing times are longer at lower temperatures and faster in warmer temperatures;
- Do not apply when temperatures may fall below 0 °C

## Technical Specifications

- Available in 20 kg and 12 kg buckets. As an example, 12 kg will point approximately 7.5m<sup>2</sup> using 600 x 600mm slabs with 10mm joint width, 24mm deep. Minimum width for slabs is 3mm with a minimum depth of 12mm and for bricks is 3mm. There is no maximum depth or width;
- The quartz base is extremely hard with a hardness rating of 7 on the Mohs scale;
- The finished product is weather resistant, fade resistant and chemical resistant;
- Colours available: Buff, Charcoal, Mushroom and Grey.
- We try to keep our colours consistent, but colours may vary between batches due to natural sand.
- Shelf life of 24 months and 12 months when opened providing bags are sealed.
- Not suitable for all types of surfaces, we recommend doing a small test prior to use.
- May cause staining on granite and some types of porcelain.

## Health and Safety

Please see GHS sticker on the side of the tub which include H302, H315, H317, H318 and H412 warnings.

Pave Fix Ltd, 10 Stag Business Park, Christchurch Road, Ringwood, Hampshire, BH24 3AS  
Website: [www.pavefix.co.uk](http://www.pavefix.co.uk) email: [info@pavefix.co.uk](mailto:info@pavefix.co.uk) Telephone: 01425 478500

Whilst Pave Fix Limited endeavours to ensure that any advice recommendations specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.